

Safety Data Sheet



SECTION 1: Identification of the substance/mixture and the company/undertaking

Revision Date: 10/08/2021
Print Date: 11/13/2021

1.1 Production identifiers

Product name : METHYL METHACRYLATE
Brand : CJ Chemicals LLC
CAS-No. : 80-62-6

1.2 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Laboratory chemicals, synthesis of substances

1.3 Details of the supplier of the safety data sheet

Company : CJ Chemicals LLC
3469 E Grand River Rd #112
Howell, MI 48843
United States

Telephone : +1 (888) 274-1044

1.4 Emergency Telephone

Emergency Phone # : 1-800-424-9300 CHEMTREC (USA)
1-703-527-3887 CHEMTREC (international) 24 hours/day; 7 days/week

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

GHS Classification in accordance with 29 CFR 1910 (OSHA HCS)

Flammable liquids (Category 2), H225
Skin irritation (Category 2), H315
Skin sensitization (Sub-category 1B), H317
Specific target organ toxicity - single exposure (Category 3), Respiratory system, H335
Short-term (acute) aquatic hazard (Category 3), H402

For the full text of the H-Statements mentioned in this Section, see Section 16.

2.2 GHS Label elements, including precautionary statements

Pictogram



Signal word

Danger

Hazard statement(s)	
H225	Highly flammable liquid and vapor.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H335	May cause respiratory irritation.
H402	Harmful to aquatic life.
Precautionary statement(s)	
P210	Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233	Keep container tightly closed.
P240	Ground/bond container and receiving equipment.
P241	Use explosion-proof electrical/ ventilating/ lighting/ equipment.
P242	Use only non-sparking tools.
P243	Take precautionary measures against static discharge.
P261	Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
P264	Wash skin thoroughly after handling.
P271	Use only outdoors or in a well-ventilated area.
P272	Contaminated work clothing must not be allowed out of the workplace.
P273	Avoid release to the environment.
P280	Wear protective gloves/ eye protection/ face protection.
P303 + P361 + P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312	IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/ doctor if you feel unwell.
P333 + P313	If skin irritation or rash occurs: Get medical advice/ attention.
P362	Take off contaminated clothing and wash before reuse.
P370 + P378	In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.
P403 + P233	Store in a well-ventilated place. Keep container tightly closed.
P403 + P235	Store in a well-ventilated place. Keep cool.
P405	Store locked up.
P501	Dispose of contents/ container to an approved waste disposal plant.

2.3 Hazards not otherwise classified (HNOC) or not covered by GHS

Lachrymator.

SECTION 3: Composition/information on ingredients

3.1 Substances

Formula	: C ₅ H ₈ O ₂
Molecular weight	: 100.12 g/mol
CAS-No.	: 80-62-6
EC-No.	: 201-297-1
Index-No.	: 607-035-00-6

Component	Classification	Concentration
methyl methacrylate		
	Flam. Liq. 2; Skin Irrit. 2; Skin Sens. 1B; STOT SE 3;	<= 100 %

	Aquatic Acute 3; H225, H315, H317, H335, H402	
--	---	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

SECTION 4: First aid measures

4.1 Description of first-aid measures

General advice

Show this material safety data sheet to the doctor in attendance.

If inhaled

After inhalation: fresh air.

In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

In case of eye contact

After eye contact: rinse out with plenty of water. Remove contact lenses.

If swallowed

After swallowing: immediately make victim drink water (two glasses at most). Consult a physician.

4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

4.3 Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Carbon dioxide (CO₂) Foam Dry powder

Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

5.2 Special hazards arising from the substance or mixture

Carbon oxides

Flash back possible over considerable distance., Container explosion may occur under fire conditions.

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up with liquid-absorbent material (e.g. Chemisorb®). Dispose of properly. Clean up affected area.

6.4 Reference to other sections

For disposal see section 13.

SECTION 7: Handling and storage

7.1 Precautions for safe handling

Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance. For precautions see section 2.2.

7.2 Conditions for safe storage, including any incompatibilities

Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Storage stability

Recommended storage temperature
2 - 8 °C

Storage class

Storage class (TRGS 510): 3: Flammable liquids

7.3 Specific end use(s)

Apart from the uses mentioned in section 1.2 no other specific uses are stipulated

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
methyl methacrylate	80-62-6	TWA	50 ppm	USA. ACGIH Threshold Limit Values (TLV)
	Remarks	Dermal Sensitization Not classifiable as a human carcinogen		
		STEL	100 ppm	USA. ACGIH Threshold Limit Values (TLV)
		Dermal Sensitization Not classifiable as a human carcinogen		
		TWA	100 ppm 410 mg/m ³	USA. NIOSH Recommended Exposure Limits
		TWA	100 ppm 410 mg/m ³	USA. Occupational Exposure Limits (OSHA) - Table Z-1 Limits for Air Contaminants
		TWA	100 ppm 410 mg/m ³	USA. OSHA - TABLE Z-1 Limits for Air Contaminants - 1910.1000
		PEL	50 ppm 205 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)
		STEL	100 ppm 410 mg/m ³	California permissible exposure limits for chemical contaminants (Title 8, Article 107)

8.2 Exposure controls

Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

Personal protective equipment

Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses Tightly fitting safety goggles

Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN374 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: www.kcl.de).

Splash contact

Material: butyl-rubber

Minimum layer thickness: 0.7 mm

Break through time: 60 min

Material tested: Butoject® (KCL 898)

Body Protection

Flame retardant antistatic protective clothing.

Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

Control of environmental exposure

Do not let product enter drains. Risk of explosion.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

- | | |
|---|--|
| a) Appearance | Form: liquid
Color: colorless |
| b) Odor | pungent |
| c) Odor Threshold | No data available |
| d) pH | No data available |
| e) Melting point/freezing point | Melting point/freezing point: ca.-48 °C (ca.-54 °F) at ca.1,013 hPa - (ECHA) |
| f) Initial boiling point and boiling range | 100.36 °C 212.65 °F at ca.1,013.25 hPa - (ECHA) |
| g) Flash point | 10 °C (50 °F) - closed cup - DIN 51755 Part 1 |
| h) Evaporation rate | No data available |
| i) Flammability (solid, gas) | No data available |
| j) Upper/lower flammability or explosive limits | Upper explosion limit: 12.5 %(V)
Lower explosion limit: 2.1 %(V) |
| k) Vapor pressure | 37 hPa at 20 °C (68 °F) - OECD Test Guideline 104 |
| l) Vapor density | ca.3.5 at 20 °C(68 °F) |
| m) Density | 0.94 g/cm ³ at 20 °C (68 °F) |
| Relative density | 0.94 at 20 °C (68 °F) |
| n) Water solubility | 15.3 g/l at 20 °C (68 °F) |
| o) Partition coefficient: n-octanol/water | log Pow: 1.38 at 20 °C (68 °F) - OECD Test Guideline 107 -
Bioaccumulation is not expected. |
| p) Autoignition temperature | 435 °C (815 °F) at 1,013.25 hPa |
| q) Decomposition temperature | No data available |
| r) Viscosity | No data available |
| s) Explosive properties | No data available |

t) Oxidizing properties none

9.2 Other safety information

Surface tension	61 mN/m - OECD Test Guideline 115
Relative vapor density	ca.3.5 at 20 °C (68 °F)

SECTION 10: Stability and reactivity

10.1 Reactivity

Vapors may form explosive mixture with air.

10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) . Polymerizes with evolution of heat. Avoid contact with incompatible materials. Unless inhibited, product can polymerize, raising temperature and pressure, possibly rupturing container. Check inhibitor content often adding to bulk liquid if needed. Do not blanket or mix with oxygen-free gas as it renders inhibitor ineffective.

10.3 Possibility of hazardous reactions

Polymerizes readily unless inhibited.

10.4 Conditions to avoid

Heat. May polymerize on exposure to light.
Warming.

10.5 Incompatible materials

rubber, various plastics, Strong oxidizing agents

10.6 Hazardous decomposition products

In the event of fire: see section 5

SECTION 11: Toxicological information

11.1 Information on toxicological effects

Acute toxicity

LD50 Oral - Rat - 7,872 mg/kg

Remarks: (RTECS)

LC50 Inhalation - Rat - male and female - 4 h - 29.8 mg/l

Remarks: (ECHA)

LC50 Inhalation - Rat - 4 h - 78,000 mg/m³

LD50 Dermal - Rabbit - male - > 5,000 mg/kg

(OECD Test Guideline 402)

No data available

Skin corrosion/irritation

Skin - Rabbit

Result: Irritating to skin. - 4 h

Remarks: (ECHA)

Serious eye damage/eye irritation

Eyes - Rabbit

Result: No eye irritation

Remarks: (ECHA)

Respiratory or skin sensitization

Local lymph node assay (LLNA) - Mouse

Result: Causes sensitization.

(OECD Test Guideline 429)

Germ cell mutagenicity

Test Type: Ames test

Test system: *S. typhimurium*

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 471

Result: negative

Test Type: in vivo assay

Species: Mouse

Application Route: Inhalation

Method: OECD Test Guideline 478

Result: negative

Carcinogenicity

IARC: No ingredient of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

NTP: No ingredient of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is on OSHA's list of regulated carcinogens.

Reproductive toxicity

No data available

Specific target organ toxicity - single exposure

Inhalation - May cause respiratory irritation.

Specific target organ toxicity - repeated exposure

No data available

Aspiration hazard

No data available

11.2 Additional Information

Repeated dose toxicity - Rat - male - Oral - NOAEL (No observed adverse effect level) - >= 124.1 mg/kg

Remarks: (ECHA)

RTECS: OZ5075000

Central nervous system depression, Drowsiness, Irritability, Dizziness, Ataxia., narcosis, To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

Liver - Irregularities - Based on Human Evidence

SECTION 12: Ecological information

12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Lepomis macrochirus (Bluegill sunfish) - 191 mg/l - 96 h Remarks: (ECHA)
	static test LC50 - Lepomis macrochirus (Bluegill sunfish) - 283 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	flow-through test NOEC - Daphnia magna (Water flea) - 48 mg/l - 48 h Remarks: (ECHA)
	flow-through test EC50 - Daphnia magna (Water flea) - 69 mg/l - 48 h Remarks: (ECHA)
Toxicity to algae	static test EC50 - Pseudokirchneriella subcapitata - > 110 mg/l - 72 h (OECD Test Guideline 201)
	static test NOEC - Pseudokirchneriella subcapitata - > 110 mg/l - 72 h (OECD Test Guideline 201)

12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 14 d Result: 94 % - Readily biodegradable. (OECD Test Guideline 301C)
Biochemical Oxygen Demand (BOD)	140 mg/g

12.3 Bioaccumulative potential

No data available

12.4 Mobility in soil

No data available

12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

12.6 Other adverse effects

SECTION 13: Disposal considerations**13.1 Waste treatment methods****Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself. See www.retrologistik.com for processes regarding the return of chemicals and containers, or contact us there if you have further questions.

SECTION 14: Transport information**DOT (US)**

UN number: 1247 Class: 3 Packing group: II
Proper shipping name: Methyl methacrylate monomer, stabilized
Reportable Quantity (RQ): 1000 lbs
Poison Inhalation Hazard: No

IMDG

UN number: 1247 Class: 3 Packing group: II EMS-No: F-E, S-D
Proper shipping name: METHYL METHACRYLATE MONOMER, STABILIZED

IATA

UN number: 1247 Class: 3 Packing group: II
Proper shipping name: Methyl methacrylate monomer, stabilized

SECTION 15: Regulatory information**SARA 302 Components**

This material does not contain any components with a section 302 EHS TPQ.

SARA 313 Components

The following components are subject to reporting levels established by SARA Title III, Section 313:

	CAS-No.	Revision Date
methyl methacrylate	80-62-6	2007-07-01

SARA 311/312 Hazards

Fire Hazard, Acute Health Hazard, Chronic Health Hazard

Massachusetts Right To Know Components

No components are subject to the Massachusetts Right to Know Act.

SECTION 16: Other information**Further information**

The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. The information in this document is based on the present state of our knowledge and is applicable to the product with regard to appropriate safety precautions. It does not represent any guarantee of the properties of the product. CJ Chemicals LLC and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See www.cjchemicals.com and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

